

# PHILIP PAYNE TRACK PRODUCT COMPATIBILITY TABLE



## LN, LM, YS, YL and XT Variants

- This applies to the GA69 adapter used in;
- LN (basic emergency non-maintained)
- LM (basic emergency maintained)
- YS (self-test emergency non-maintained)
- YL (self-test emergency maintained)
- XT (Specto-XT emergency non-maintained/maintained)
- 230V AC supply only.
- For the TYKE Track luminaire, Nordic Aluminium XTAK 144-1 fixing are used to secure the luminaire to the track.

|                  |                                           |   |
|------------------|-------------------------------------------|---|
| Nordic Aluminium | Global Pro (XTS4), 3-circuit track        | ✓ |
| Nordic Aluminium | Global Pro (XTSF4), 3-circuit track       | ✓ |
| Nordic Aluminium | Old Nokia (XTS and XTTS), 3-circuit track | ✓ |

## DN and DL Variants

- This applies to the GAC69 adapter used in;
- DN (DALI emergency non-maintained)
- DL (DALI emergency maintained)
- 230V AC supply only.
- For the TYKE Track luminaire, Nordic Aluminium XTAK 144-1 fixing are used to secure the luminaire to the track.

|                  |                                        |   |
|------------------|----------------------------------------|---|
| Nordic Aluminium | Global Pulse (XTSC6), 3-circuit track  | ✓ |
| Nordic Aluminium | Global Pulse (XTSCF6), 3-circuit track | ✓ |

Please contact the Philip Payne Technical department if other track systems are specified. [technical@philippayne.co.uk](mailto:technical@philippayne.co.uk).